

## ROAD RACING and SUPERMOTO RANGE 2019

		<b>METZELER</b> SHARING INDEPENDENCE		RIM	WIDTH	DIAMETER	DIAMETER	WEIGHT	COLD PRESSURE	HOT PRESSURE	WARMERS
		recommended (inches)	mm (inches)	centre mm (inches)	shoulder mm (inches)	kgs (lbs/pound)	recommended range (w/o warmers) bar (psi)	recommended range (after warmers) bar (psi)	usage °C (°F)		
<b>RACETEC RR SLICK</b>											
<b>D R Y</b>	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	50 mins. @ 80°C (176°F)	
		rear 180/60 R17	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
		rear 200/60 R17	6.00	200 (7.87)	662 (26.06)	530 (20.87)	6.7 (14.7)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
<b>RACETEC RR SLICK COMPK</b>											
<b>S L I C K</b>	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.1/2.2 (30/32)	2.2/2.5 (32/36)	50 mins. @ 80°C (176°F)	
		rear 180/60 R17	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
		rear 200/55 R17	6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
<b>RACETEC SM</b>											
<b>R A I N</b>	16.5"	front 125/75 R420	3.50	120 (4.72)	600 (23.62)	489 (19.25)	4.4 (9.7)	1.6/1.8 (23/26)	1.8/1.9 (26/28)	40 mins. @ 80°C (176°F)	
	17"	front 125/75 R17	3.50	120 (4.72)	604 (23.77)	499 (19.64)	4.3 (9.5)	1.6/1.8 (23/26)	1.8/1.9 (26/28)		
		rear 165/55 R17	5.00 - 5.50	162 (6.38)	631 (24.84)	521 (20.51)	5.4 (11.9)	1.5/1.6 (22/23)	1.6/1.7 (23/25)		
<b>RACETEC SM RAIN</b>											
<b>R A I N</b>	16.5"	front 125/75 R420	3.50	120 (4.72)	600 (23.62)	489 (19.25)	4.4 (9.7)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)	
	17"	front 125/75 R17	3.50	120 (4.72)	604 (23.77)	499 (19.64)	4.3 (9.5)	2.3 (34)	2.4 (35)		
		rear 165/55 R17	5.50	162 (6.38)	631 (24.84)	521 (20.51)	5.6 (12.3)	1.9 (28)	2.0 (29)		
<b>RACETEC RR</b>											
<b>D R Y</b>  <b>D O T</b>	17"	front 120/70 ZR17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.0/2.2 (29/32)	2.1/2.4 (30/35)	50 mins. @ 80°C (176°F)	
		rear 160/60 ZR17	4.50 - 5.00	165 (6.50)	631 (24.84)	521 (20.51)	5.6 (12.4)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
		rear 180/55 ZR17	5.50	181 (7.12)	641 (25.23)	529 (20.83)	5.8 (12.8)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
		rear 180/60 ZR17	5.50	190 (7.48)	656 (25.83)	527 (20.75)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
		rear 200/55 ZR17	6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.5 (14.3)	1.6/1.8 (23/26)	1.7/1.9 (25/28)		
	18"	front 110/80 ZR18	2.15 - 2.50	114 (4.49)	632 (24.88)	545 (21.45)	4.8 (10.5)	2.0/2.2 (29/32)	2.1/2.4 (30/35)		
		rear 150/65 ZR18	3.50 - 4.00	160 (6.29)	648 (25.51)	552 (21.73)	6.5 (14.3)	1.7/1.9 (25/28)	1.8/2.0 (26/29)		
rear 160/60 ZR18	4.00 - 4.50	164 (6.46)	648 (25.51)	554 (21.81)	6.5 (14.3)	1.7/1.9 (25/28)	1.8/2.0 (26/29)				
<b>RACETEC RAIN</b>											
<b>R A I N</b>	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.3 (9.5)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)	
		rear 180/55 R17	5.50	181 (7.12)	641 (25.23)	527 (20.75)	6.4 (14.1)	1.9 (28)	2.0 (29)		
		rear 190/60 R17	5.50 - 6.00	193 (7.60)	656 (25.83)	531 (20.90)	7.1 (15.6)	1.9 (28)	2.0 (29)		
<b>RACETEC INTERMEDIATE</b>											
<b>I N T E R</b>	17"	front 120/70 R17	3.50	120 (4.72)	604 (23.78)	501 (19.72)	4.2 (9.3)	2.3 (34)	2.4 (35)	30 mins. @ 50°C (122°F)	
		rear 190/60 R17	5.50 - 6.00	193 (7.60)	656 (25.83)	531 (20.90)	6.7 (14.8)	1.9 (28)	2.0 (29)		